




SECHSKANT-BLECHSCHRAUBEN
MIT LÄNGSSCHLITZ - KOPF SCHARFKANTIG ABGEGRATET

HEXAGON HEAD SELF TAPPING SCREWS
WITH SLOT - SHARP SHAPED HEAD

VIS À TÔLE-TÊTE HEXAGONALE
AVEC FENTE - BOUT POINTU

		
A2 W.-Nr. 1.4301/03 AISI 304/02 A2 W.-Nr. 1.4301/03 AISI 304/02 A2 W.-Nr. 1.4301/03 AISI 304/02	Polyamid Polyamide Polyamide	EPDM / A2 W.-Nr. 1.4301/03 AISI 304/02 EPDM / A2 W.-Nr. 1.4301/03 AISI 304/02 EPDM / A2 W.-Nr. 1.4301/03 AISI 304/02

Ø 4,2 mm

SW = 7 mm
L = 9,5 bis 25,0 mm -0,8 / +0,8 mm
= C

													
			CODE	P	D			CODE	P	D			CODE
4,2 x 9,5 mm	1000	18000	20301 42950	2,0 mm	10,0 mm	1000	18000	20302 42950	3,0 mm	12,0 mm	500	12000	20304 42950
4,2 x 13 mm	1000	16000	20301 42130	2,0 mm	10,0 mm	1000	16000	20302 42130	3,0 mm	12,0 mm	500	12000	20304 42130
4,2 x 16 mm	1000	12000	20301 42160	2,0 mm	10,0 mm	500	12000	20302 42160	3,0 mm	12,0 mm	500	10000	20304 42160
4,2 x 19 mm	1000	12000	20301 42190	2,0 mm	10,0 mm	500	12000	20302 42190	3,0 mm	12,0 mm	500	8000	20304 42190
4,2 x 25 mm	500		20301 42250	2,0 mm	10,0 mm	500		20302 42250	3,0 mm	12,0 mm	500	12000	20304 42250

Ø 4,8 mm

SW = 8 mm
L = 9,5 bis 25,0 mm -0,8 / +0,8 mm
= C

4,8 x 9,5 mm	1000 20301 48950	2,0 mm 10,0 mm	1000 20302 48950	3,0 mm 12,0 mm	500 20304 48950
4,8 x 13 mm	1000 12000 20301 48130	2,0 mm 10,0 mm	1000 12000 20302 48130	3,0 mm 12,0 mm	500 8000 20304 48130
4,8 x 16 mm	1000 12000 20301 48160	2,0 mm 10,0 mm	500 11000 20302 48160	3,0 mm 12,0 mm	500 8000 20304 48160
4,8 x 19 mm	500 8000 20301 48190	2,0 mm 10,0 mm	500 10000 20302 48190	3,0 mm 12,0 mm	500 8000 20304 48190
4,8 x 25 mm	500 6000 20301 48250	2,0 mm 10,0 mm	500 20302 48250	3,0 mm 12,0 mm	250 6000 20304 48250

Ø 5,5 mm

SW = 8 mm
L = 9,5 bis 25,0 mm -0,8 / +0,8 mm
= C

5,5 x 16 mm	500 20301 55160	2,0 mm 11,0 mm	500 20302 55160	3,0 mm 16,0 mm	250 20304 55160
5,5 x 19 mm	500 20301 55190	2,0 mm 11,0 mm	500 20302 55190	3,0 mm 16,0 mm	250 20304 55190
5,5 x 25 mm	500 20301 55250	2,0 mm 11,0 mm	250 20302 55250	3,0 mm 16,0 mm	250 20304 55250

Ø 6,3 mm

SW = 10 mm
L = 9,5 bis 25,0 mm -0,8 / +0,8 mm
= C

6,3 x 16 mm	500 20301 63160	2,0 mm 12,5 mm	500 20302 63160	3,0 mm 16,0 mm	250 20304 63160
6,3 x 19 mm	500 2000 20301 63190	2,0 mm 12,5 mm	500 20302 63190	3,0 mm 16,0 mm	250 20304 63190
6,3 x 25 mm	250 20301 63250	2,0 mm 12,5 mm	250 12000 20302 63250	3,0 mm 16,0 mm	250 20304 63250